

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 23,  
T. 25 S., R. 4 W., Willamette Meridian, Oregon

17778

**CHAINS**

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 4 W  
C 1/4  
S 23  
1983

from which

A hemlock, 9 ins. diam., bears S. 35 1/2° E.,  
15 lks. dist., mkd. C 1/4 S23 BT.

A hemlock, 12 ins. diam., bears N. 49 1/2° W.,  
18 lks. dist., mkd. C 1/4 S23 BT.

Descend over NE. slope.

- 41.05 Ravine, drains N. 70° E.; asc. over SE. slope.
- 48.95 Spur, slopes N. 70° E.; desc. over broken NE. slope, changing to E. slope.
- 69.40 Norris Creek, 6 lks. wide, course N. 30° W.; asc. SW. slope.
- 70.10 Spur, slopes S. 80° W.; desc. over broken NW. slope.
- 78.64 The 1/4 sec. cor. of secs. 14 and 23.

From the 1/4 sec. cor. of secs. 23 and 24.

N. 89° 40' W., on the E. and W. center line of sec. 23.

Ascend over E. slope, through scattering timber and dense undergrowth.

- 8.30 Ridge, bears N. 5° W. and S. 15° E., also dirt road, 15 lks. wide, bears same; desc. over SW. slope, changing to W. slope.
- 11.55 Dirt road, 15 lks. wide, bears N. 35° E. and S. 5° W.
- 26.60 Gravelled road, 15 lks. wide, bears N. 35° E. and S. 10° E., in curve.
- 32.70 Norris Creek, 5 lks. wide, course N. 25° W.; asc. over NE. slope.
- 38.63 The center 1/4 sec. cor. of sec. 23.  
  
Ascend over NE. slope, changing to E. slope.
- 57.10 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
- 57.85 Ridge, bears N. and S.; desc. over NW. slope.
- 58.37 Point for the center W 1/16 sec. cor. of sec. 23.  
  
Set an iron post, 18 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16  
C ——— C  
S 23  
1983