

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 23,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

17780

CHAINS	
19.54	The SW 1/16 sec. cor. of sec. 23.
26.55	Ravine, drains S. 10° W.; asc. over SE. slope.
33.60	Spur, slopes S. 30° W.; desc. SW. slope.
39.01	The S 1/16 sec. cor. of secs. 22 and 23.
<p>From the center W 1/16 sec. cor. of sec. 23.</p> <p>N. 2° 15' E., on the N. and S. center line of the NW 1/4 of sec. 23.</p> <p>Descend over N. slope, changing to NE. slope, through heavy timber and dense undergrowth.</p>	
10.15	Ravine, drains E.; asc. over SE. slope.
24.65	Spur, slopes N. 50° E.; desc. NE. slope.
29.65	Ravine, drains N. 20° E.; asc. SE. slope.
35.80	Spur, slopes N. 15° E.; desc. NW. slope.
39.98	The W 1/16 sec. cor. of secs. 14 and 23.
<p>Subdivision of Section 27, T. 25 S., R. 4 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 09' W., on the N. and S. center line of sec. 27.</p> <p>Ascend over SE. slope, changing to S. slope, through heavy timber and dense undergrowth.</p>	
3.90	Dirt road, 10 lks. wide, bears N. 10° E. and S. 30° W.
18.72	Point for the center S 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} C \\ S\ 1/16 \quad \quad S\ 27 \\ C \\ 1983 \end{array} $
	from which
	A cedar, 16 ins. diam., bears N. 43° E., 50 lks. dist., mkd. CS 1/16 S27 BT.
	A fir, 12 ins. diam., bears N. 62° W., 32 lks. dist., mkd. CS 1/16 S27 BT.
	Ascend over SE. slope.
23.00	Gravel road, 15 lks. wide, bears N. 50° W. and S. 70° E.
32.05	Ridge, bears E. and W.; desc. NW. slope.