

# County Surveyor's Record, Douglas County, Oregon

17787

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

## CHAINS

A fir, 16 ins. diam., bears N. 41° W., 25 lks.  
dist., with scribe mark 2 visible on opened blaze.

and bearing trees mkd. by Evans

A fir, 14 ins. diam., bears N. 23 1/2° E.,  
20 lks. dist., with healed double blaze.

A fir, 17 ins. diam., bears N. 58° W.,  
50 lks. dist., with healed double blaze.

From this point, the 1/4 sec. cor. of sec. 32 only, bears  
S. 89° 37' E., 0.440 chs. dist., perpetuated and recorded  
by Arthur R. Evans, Deputy County Surveyor, in 1951,  
further perpetuated by John M. Powell, Deputy County  
Surveyor, in 1968, monumented with an iron post, 1 1/4 ins.  
diam., firmly set, projecting 10 ins. above ground, with  
brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 2 W

1/4 S 32

1968

from which the remaining bearing tree mkd. by Mensch

A madrone, 14 ins. diam., bears S. 64° E., 50 lks.  
dist., with fragmentary scribe marks visible  
on opened blaze. (Record, S. 60° E.)

and the remains of a bearing tree mkd. by Evans

A fir rootcrown, size indeterminate, bears  
S. 82 1/2° E., 33 lks. dist., no marks visible.

and bearing trees mkd. by Powell

A fir, 13 ins. diam., bears S. 50° E., 18  
lks. dist., with healed double blaze.

A fir, 13 ins. diam., bears S. 46 1/2° W.,  
56 lks. dist., with healed double blaze.

N. 89° 46' W., on the S. bdy. of sec. 29, marking and  
blazing the true line.

Ascend over broken SE. slope, through scattering timber  
and dense undergrowth.

13.50 Spur, slopes S. 20° E.; desc. over broken SW. slope.

20.07 Point for the W 1/16 sec. cor. of sec. 29 only.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in an  
iron pipe, 15 ins. long, 1 in. diam., 25 ins. in the  
ground, in concrete, the top 10 ins. below road surface,  
with top mkd.

W 1/16 S 29

1983

from which

A fir, 11 ins. diam., bears N. 9° E.,  
46 1/2 lks. dist., mkd. W 1/16 S29 BT.