

County Surveyor's Record, Douglas County, Oregon

17789

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 4 ins. diam., bears N. 63° E., 56 lks. dist., mkd. X BT.</p> <p>A fir, 15 ins. diam., bears N. 34 1/2° W., 81 lks. dist., mkd. T30S R2W S30 BT.</p> <p>From this point, the United States Coast and Geodetic Survey station H-500, bears S. 81° 27' E., 108.35 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., set in concrete block, 2 ft. sq., with top mkd. UNITED STATES COAST AND GEODETIC SURVEY H 500 1949. The coordinates of this point were determined by the Douglas County Surveyor's Office, in 1975.</p> <p>Land, mountainous. Soil, rocky clay. Timber, madrone, fir, hemlock, pine, oak, and alder; undergrowth, poison oak, salal, Oregon grape, ferns, arrowwood, hazel, blackberry, salmonberry, and young timber.</p>
	<p>Subdivision of Section 29, T. 30 S., R. 2 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of sec. 29 only.</p> <p>N. 0° 10' E., on the N. and S. center line of sec. 29.</p> <p>Ascend over broken SE. slope, changing to SW. slope, through heavy timber and dense undergrowth.</p>
2.80	<p>Three wire power transmission line, bears E. and W.</p>
40.10	<p>Spur, slopes S. 30° E.; asc. over broken SE. slope.</p>
40.34	<p>Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 2 W C 1/4 S 29 1983</p> <p>from which</p> <p>A fir, 22 ins. diam., bears N. 12° E., 60 lks. dist., mkd. C 1/4 S29 BT.</p> <p>A pine, 36 ins. diam., bears N. 38 1/2° W., 31 lks. dist., mkd. C 1/4 S29 BT.</p> <p>Ascend over broken SE. slope.</p>
52.55	<p>Spur, slopes S. 40° W.; asc. over broken SW. slope.</p>
77.45	<p>Spur, slopes S. 50° W.; desc. over NW. slope.</p>
80.57	<p>The 1/4 sec. cor. of sec. 29 only, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1970, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>