

County Surveyor's Record, Douglas County, Oregon

17790

Subdivision of Section 29,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 30 S R 2 W
1/4 S 29
1970

from which the remains of an original bearing tree

A madrone snag, 26 ins. diam., bears S. 40° W.,
9 lks. dist., with scribemarks BT visible on
opened blaze.

and bearing trees mkd. by Powell

A madrone, 10 ins. diam., bears S. 11° W., 51
lks. dist., with scribe marks 1/4 S29 CS BT
visible on open blaze.

A fir, 15 ins. diam., bears S. 66° W., 41
lks. dist., with healed double blaze.

From this point, the 1/4 sec. cor. of sec. 20 only, bears
S. 86° 42' E., 0.235 chs. dist., perpetuated and recorded
by John M. Powell, Deputy County Surveyor, in 1970, monu-
mented with an iron post, 1 1/4 ins. diam., firmly set,
projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 2 W
1/4 S 20
1970

from which the remains of bearing trees mkd. by Mensch

A madrone, 24 ins. diam., bears N. 6° E.,
40 lks. dist., no marks visible.

A cedar snag, 18 ins. diam., bears N. 17° W.,
11 lks. dist., axe marks visible.

and the remains of bearing trees mkd. by Powell

A fir snag, 34 ins. diam., bears N. 80° E.,
61 lks. dist., with scribe marks 1/4 S20 CS BT
visible on open blaze.

A fir, 36 ins. diam., bears N. 10 1/2° W.,
16 lks. dist., with healed blaze.

From the 1/4 sec. cor. of secs. 28 and 29, perpetuated and
recorded by John M. Powell, Deputy County Surveyor, in
1968, monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 2 W
1/4 S 29 | S 28
1968

from which the original bearing trees

A white oak, 23 ins. diam., bears N. 3° E.,
115 lks. dist., with axe marks visible on
opened blaze.

A white oak, 23 ins. diam., bears N. 18° W.,
105 lks. dist., with healed double blaze.