

County Surveyor's Record, Douglas County, Oregon

17791

Subdivision of Section 29,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	and bearing trees mkd. by Powell
	A white oak, 11 ins. diam., bears N. 24° E., 55 lks. dist., with healed double blaze.
	A fir, 29 ins. diam., bears S. 87° W., 30 lks. dist., with healed double blaze.
	N. 89° 51' W., on the E. and W. center line of sec. 29.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
4.50	Spur, slopes S. 10° W.; desc. over SW. slope.
18.05	Slate Creek, 5 lks. wide, course S. 25° W.; asc. over broken NE. slope.
40.27	The center 1/4 sec. cor. of sec. 29.
	Ascend over NE. slope.
40.35	Spur, slopes S. 30° E.; desc. over broken SW. slope.
60.42	Point for the center W 1/16 sec. cor. of sec. 29.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	C $\frac{W \ 1/16}{S \ 29}$ C 1983
	from which
	A fir, 20 ins. diam., bears N. 70° E., 15 1/2 lks. dist., mkd. CW 1/16 S29 BT.
	A fir, 12 ins. diam., bears N. 40° W., 27 lks. dist., mkd. CW 1/16 S29 BT.
	Descend over SW. slope.
63.55	Head of ravine, drains S.; asc. over SE. slope.
69.25	Spur, slopes S.; desc. over SW. slope.
78.25	Ravine, drains S. 5° W.; asc. over SE. slope.
80.57	The 1/4 sec. cor. of secs. 29 and 30, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, alongside of which is a basalt stone, 14 x 10 x 4 ins., firmly set, 12 ins. in the ground, mkd. 1/4 of W. face, with brass cap on iron post mkd.
	COUNTY SURVEYORS OFFICE T 30 S R 2 W 1/4 S 30 S 29 1968
	from which the remains of bearing trees mkd. by Powell
	A sawed pine stump, 25 ins. diam., bears S. 86° E., 314 lks. dist., with scribe marks 1/4 S29 BT visible on open blaze.