

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

17792

**CHAINS**

A pine, 24 ins. diam., bears N. 73° W.,  
83 lks. dist., with healed blaze.

and a new bearing tree

A pine, 16 ins. diam., bears N. 34 1/2° E.,  
173 lks. dist., mkd. 1/4 S29 BT.

From the W 1/16 sec. cor. of sec. 29 only.

N. 0° 03' E., on the N. and S. center line of the SW 1/4 of  
sec. 29.

Ascend over broken SW. slope, through heavy timber and  
dense undergrowth.

11.80

Three wire, power transmission line, bears N. 65° W. and  
S. 65° E.

40.32

The center W 1/16 sec. cor. of sec. 29.

**GENERAL DESCRIPTION**

The area covered by this resurvey is located about  
one mile northwesterly from Tiller, Oregon. The portion  
of the township resurveyed is located in mountainous  
country, with elevations ranging from about 2,350 feet  
above sea level near the 1/4 section corner of section 29  
only, on the north boundary of the section, to about  
1,250 feet above sea level at the corner of sections 29  
and 30 only. The area is drained by Slate Creek and  
numerous seasonal drainages flowing southerly to the  
South Umpqua River. The soil is made up of a rocky clay.

The timber consists of pine, fir, madrone, oak,  
hemlock, yew, alder, cedar, maple, and chinquapin. The  
undergrowth is made up of Oregon grape, arrowwood, hazel,  
poison oak, salmonberry, blackberry, huckleberry,  
thimbleberry, salal, ferns, wild rose, and young timber.

The area resurveyed is reached by way of State  
Highway No. 42, with gravelled and dirt roads branching  
from it into the area. No mineral deposits were noted  
during the resurvey.

The average of a number of readings along the lines  
resurveyed gives a value of 19° 45' East for the mean  
magnetic declination. There is a range of 1° due to  
local attraction.