

County Surveyor's Record, Douglas County, Oregon

17795

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Beginning at the E 1/16 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

E 1/16 $\frac{S \ 30}{S \ 31}$
1960

from which bearing trees mkd. by Brooks

A fir, 31 ins. diam., bears N. 2 3/4° E., 138 lks. dist., with healed blaze. (Record, N. 1° E., 135 lks.)

A fir, 17 ins. diam., bears S. 38° W., 36 lks. dist., with healed blaze.

S. 89° 26' W., bet. secs. 30 and 31, marking the true line.

Ascend over NE. slope.

2.35

Spur, slopes NW.; desc. over broken SW. slope.

19.93

The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4 $\frac{S \ 30}{S \ 31}$
T 22 S R 8 W
1960

from which bearing trees mkd. by Brooks

A fir, 24 ins. diam., bears N. 87° E., 96 lks. dist., with healed blaze. (Record, N. 86° E.)

A fir, 24 ins. diam., bears S. 6 3/4° E., 121 lks. dist., with healed blaze. (Record, S. 8° E.)

Subdivision of Section 31,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

Beginning at the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 22 S R 8 W
 $\frac{1/4 \ S \ 31}{T \ 23 \ S \ R \ 8 \ W}$
1980

from which bearing trees mkd. by Wofford

A fir, 13 ins. diam., bears N. 4° E., 77 lks. dist., with scribe marks 1/4 S31 BT visible on partially healed blaze.

A fir, 17 ins. diam., bears N. 58 3/4° W., 119 1/2 lks. dist., with scribe mark X visible on partially healed breast high blaze and scribe marks BT visible on partially healed blaze at base.