

County Surveyor's Record, Douglas County, Oregon

17297

Subdivision of Section 31,
T. 22 S., R. 8 W., Willamette Meridian, Oregon

CHAINS										
	and bearing trees mkd. by Brooks									
	A fir, 20 ins. diam., bears N. 35° E., 31 lks. dist., with healed blaze. (Record, N. 34° E.)									
	A fir, 24 ins. diam., bears S. 46° W., 57 lks. dist., with healed blaze. (Record, S. 44° W.)									
	S. 89° 15' W., on the E. and W. center line of sec. 31.									
	Ascend over SE. slope, through heavy timber and dense undergrowth.									
13.30	Ridge, bears N. 20° W. and S. 20° E.; desc. over SW. slope.									
19.995	Point for the center E 1/16 sec. cor. of sec. 31.									
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.									
	<table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">C</td> <td style="text-align: center; border: 1px solid black; padding: 2px;">E 1/16</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="text-align: center; border: 1px solid black; padding: 2px;">S 31</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 2px;">1983</td> <td></td> </tr> </table>	C	E 1/16	C		S 31			1983	
C	E 1/16	C								
	S 31									
	1983									
	from which									
	A fir, 17 ins. diam., bears S. 13 1/2° E., 45 lks. dist., mkd. CE 1/16 S 31 BT.									
	A fir, 14 ins. diam., bears N. 39° W., 51 1/2 lks. dist., mkd. CE 1/16 S31 BT.									
	Descend over SW. slope.									
29.65	Creek, 2 lks. wide, course N. 30° W.; asc. over NE. slope.									
39.99	The center 1/4 sec. cor. of sec. 31.									
	Descend over NW. slope.									
43.65	Creek, 1 lk. wide, course N.; asc. over NE. slope.									
52.25	Ridge, bears N. 20° W. and S. 25° E.; desc. over SW. slope.									
59.70	Lutsinger Creek Road, gravelled, 20 lks. wide, bears N. 70° W. and S. 55° E., in a curve.									
70.95	Bottom of descent, slopes S.; asc. over SE. slope.									
79.25	Lutsinger Creek Road, gravelled, 20 lks. wide, bears N. 55° E. and S. 55° W.									
86.01	The 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.									
	<table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">T 22 S</td> <td style="border: none;"></td> <td style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">R 9 W</td> <td style="text-align: center; border: 1px solid black; padding: 2px;">1/4 S 31</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td></td> <td style="text-align: center; padding: 2px;">1980</td> <td></td> </tr> </table>	T 22 S		R 8 W	R 9 W	1/4 S 31			1980	
T 22 S		R 8 W								
R 9 W	1/4 S 31									
	1980									
	from which bearing trees mkd. by Wofford									
	A fir, 5 ins. diam., bears N. 82 1/2° E., 9 lks. dist., with scribe mark X visible on breast high blaze and scribe marks BT visible on partially healed blaze at base.									