

# County Surveyor's Record, Douglas County, Oregon

12801

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

A steel fence post, loosely set, projecting 5 ft. above ground, with brass cap is mkd.

1/4  $\frac{S 2}{S 11}$   
1954

from which the remaining original bearing tree

A fir, 40 ins. diam., bears N. 60° E., 4 lks. dist., with opened blaze, no marks visible.

and a bearing tree mkd. by Lytle, Norseth, Tillman, Bicknell, Gawron, and Thielsen

A fir, 33 ins. diam., bears N. 48 1/2° E., 45 lks. dist., with healed blaze.

and a new bearing tree

A maple, 21 ins. diam., bears S. 66 1/4° E., 118 lks. dist., mkd. 1/4 S11 BT.

N. 89° 28' W., bet. secs. 2 and 11, marking and blazing the true line.

Ascend over NE. slope, through heavy timber and dense undergrowth.

1.10 Spur, slopes N. 15° E.; desc. over NW. slope

9.05 Left bank of Smith River, bears N. 50° E. and S. 50° W., course S. 50° W., thence across river.

10.95 Right bank of Smith River, bears N. 50° E. and S. 50° W.; continue over nearly level land.

12.75 Smith River Road, paved, 35 lks. wide, bears N. 70° W. and S. 70° W.; asc. over SE. slope.

19.40 Creek, 2 lks. wide, wide, course S. 30° E.; asc. over SE. slope.

20.225 Point for the W 1/16 sec. cor. of secs. 2 and 11.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16  $\frac{S 2}{S 11}$   
1983

from which

A fir, 55 ins. diam., bears N. 6° E., 35 lks. dist., mkd. W 1/16 S2 BT.

A fir, 42 ins. diam., bears S. 21° W., 82 lks. dist., mkd. W 1/16 S11 BT.

Ascend over broken SE. slope.

40.45 The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.