

# County Surveyor's Record, Douglas County, Oregon

17802

Subdivision of Section 2,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 21 S    R 8 W  
C 1/4    S 2

1983

from which

A fir, 4 ins. diam., bears S. 24° E., 32 lks.  
dist., mkd. XBT.

A rock face, 15 ft. high, 20 ft. wide, bears  
S. 63 1/2° W., 16 lks. dist., mkd. XBO.

Descend over NE. slope.

43.80    Creek, 10 lks. wide, course S. 50° E.; asc. over  
SW. slope.

67.35    Dirt road, 15 lks. wide, bears N. 20° W. and  
S. 20° E.

80.60    The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of  
the tp., monumented with an iron post, 1 in. diam.,  
firmly set, projecting 4 ins. above ground, with brass  
cap mkd.

1/4      S 35  
          S 2

1950

from which the remains of bearing trees mkd. by Tillman

A hemlock snag, 13 ins. diam., bears N. 16° E.,  
41 lks. dist., with scribe marks 1/4 S35 BT  
visible on open blaze.

A fir, 26 ins. diam., bears S. 83 1/2° W.,  
19 lks. dist., with healed blaze.

and a new bearing tree

A fir, 4 ins. diam., bears N. 2 1/2° W.,  
58 1/2 lks. dist., mkd. X BT.

From the 1/4 sec. cor. of secs. 1 and 2, monumented  
with an iron post, 1 in. diam., firmly set, projecting  
10 ins. above ground, alongside of which is a steel  
fence post, loosely set, projecting 5 ft. above ground,  
with brass cap mkd.

1/4  
S 2 | S 1

1954

from which the remains of a bearing tree mkd. by Lytle,  
Norseth, Tillman, Bicknell, Gawron, and Thielsen

A fir snag, 9 ins. diam., bears S. 12° E.,  
14 lks. dist., with healed blaze.  
(Record, S. 8° E.)

and new bearing trees