

# County Surveyor's Record, Douglas County, Oregon

17804

Subdivision of Section 2,  
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 4 ins. diam., bears S. 82° E., 17 1/2 lks. dist., mkd. X BT.</p> <p>A fir, 5 ins. diam., bears S. 45° W., 24 lks. dist., mkd. 1/4 S2 BT.</p> <p>From this point, United States Geological Survey Triangulation Station "VINCENT" 1940 bears S. 45° 30' 33" W., 359.90 chs. dist., monumented with a standard brass disk, 3 ins. diam., firmly set. flush with ground, with top mkd. VINCENT 1940 and a triangle.</p> <p>N. 89° 14' W., on the E. and W. center line of sec. 2.</p> <p>Ascend over NE. slope, through heavy fir reproduction and dense undergrowth.</p>
5.40	Spur, slopes S. 50° E.; asc. over SE. slope.
12.35	Spur, slopes S. 50° W.; desc. over NW. slope.
30.80	Gravelled road, 20 lks. wide, bears N. 55° E, and S. 40° W.
35.40	Creek, 10 lks. wide, course S. 20° W.; asc. over NE. slope.
40.57	The center 1/4 sec. cor. of sec. 2.  Ascend over NE. slope.
59.50	Saddle in spur, bears N. 20° W. and S. 20° E.; desc. over SW. slope.
59.50	Abandoned gravelled road, 20 lks. wide, bears N. 35° W. and S. 20° E.
60.50	Point for the center W 1/16 sec. cor. of sec. 2.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>C    <u>W 1/16</u>    C</p> <p style="margin-left: 100px;">S 2</p> <p style="margin-left: 100px;">1983</p>
	<p>from which</p> <p>A fir, 6 ins. diam., bears N. 34 1/2° E., 34 1/2 lks. dist., mkd. CW 1/16 S2 BT.</p> <p>A fir, 5 ins. diam., bears S. 71 3/4° W., 22 lks. dist., mkd. CW 1/16 S2 BT.</p> <p>The corner is located in edge of timber, bears S. and W.</p> <p>Descend over SW. slope, along N. edge of timber.</p>
73.40	Ravine, drains S. 20° E.; asc. over SE. slope.
80.43	The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, alongside of which is a steel fence post, firmly set, projecting 4 feet above ground, with brass cap mkd.