

County Surveyor's Record, Douglas County, Oregon


Subdivision of Section 33,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

17810

CHAINS

From the 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



from which the remains of an original bearing tree

A decayed fir stump, 14 ins. diam., bears
N. 30° E., 41 lks. dist., no marks visible.

and bearing trees mkd. by Tracy

A fir, 28 ins. diam., bears S. 25° E., 39 lks.
dist., with healed double blaze.

A fir, 28 ins. diam., bears S. 28° W., 58 lks.
dist., with healed double blaze.

N. 89° 56' W., on the E. and W. center line of sec. 33.

Descend over W. slope, through heavy timber and dense undergrowth.

20.20 Creek, 2 lks. wide, course N. 10° E.; asc. over NE. slope.

28.40 Ridge, bears N. 10° E. and S. 15° W.; desc. over NW. slope.

40.10 The center 1/4 sec. cor. of sec. 33.

Descend over NW. slope.

52.50 Dirt road, 15 lks. wide, bears S. 25° E. and N. 25° W.

60.45 Enter pasture; desc. slightly over nearly level land.

70.35 Driver Valley Road, asphalt surface, 30 lks. wide, bears N. 45° E. and S. 45° W.

76.85 Creek, 5 lks. wide, course S. 45° W.; asc. slightly over nearly level land.

79.94 The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, the top 12 ins. below the surface of the ground, with brass cap mkd.

