

County Surveyor's Record, Douglas County, Oregon

17813

T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 21 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The east boundary was surveyed by Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, in 1855.

A portion of the east boundary was resurveyed and a portion of the subdivisional lines was surveyed by William P. Wright, U.S. Deputy Surveyor, in 1884.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 13, 1983, under Group Number 1158, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding public lands were blazed. All lines not forming closures were measured twice to preclude error.

The geographic position of the corner of sections 7, 12, 13, and 18, on the east boundary of the township, as scaled from the Crow, Oregon quadrangle map, prepared by the United States Geological Survey in 1942, is as follows:

Latitude 43° 45.1' N. Longitude 123° 20.8' W.

The mean magnetic declination is 19 1/4° E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon.

(Restoring the survey by Harvey Gordon and Charles T. Gardner, in 1855, and the resurvey and survey by William P. Wright in 1884)

Beginning at the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S
S 12 | S 7
S 13 | S 18
R 6 W | R 5 W
1961

from which the remains of the original bearing trees