

County Surveyor's Record, Douglas County, Oregon

17814

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 40 ins. diam., bears
N. 47° E., 11 lks. dist., no marks visible.
(Record, 8 lks.)

A sawed fir stump, 30 ins. diam., bears
S. 67 3/4° E., 14 lks. dist., with scribe
marks T21S R5W S18 BT visible. (Record,
S. 54° E., 16 lks.)

A cedar, 27 ins. diam., bears N. 75° W., 35 lks.
dist., with scribe marks T S visible on opened
blaze.

and bearing trees mkd. by Godfrey

A fir, 22 ins. diam., bears S. 19° E.,
71 lks. dist., with healed double blaze.

A fir, 37 ins. diam., bears S. 65° W.,
46 lks. dist., with healed double blaze.

A fir, 29 ins. diam., bears S. 88 1/4° W.,
65 lks. dist., with healed double blaze.

and a bearing tree mkd. by Tracy

A chinquapin, 9 ins. diam., bears N. 75° E.,
29 lks. dist., with scribe marks T21S R5W S7 BT
visible on partially healed blaze.

S. 86° 24' W., bet. secs. 12 and 13, marking and
blazing the true line.

Descend over NW. slope, through heavy timber and dense
undergrowth.

6.95 Alder Creek, 5 lks. wide, course N. 20° E.; asc. over
nearly level land.

11.65 Creek, 5 lks. wide, course S. 25° E.; asc. over broken
NE. slope.

28.80 Spur, slopes S. 50° E.; desc. over W. slope.

33.90 Ravine, drains S. 5° E.; asc. over SE. slope.

38.50 Spur, slopes N. 20° E.; desc. over NW. slope.

39.97 The 1/4 sec. cor. of secs. 12 and 13, determined from
the remains of the original bearing trees:

A sawed fir stump, 48 ins. diam., bears N. 31° E.,
23 lks. dist., with scribe marks 1/4 S12 BT
visible on opened blaze.

A decayed fir stump, 34 ins. diam., bears
S. 50° E., 61 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25
ins. in the ground, with brass cap mkd.

T 21 S R 6 W
1/4 S 12
 S 13
 1983