

County Surveyor's Record, Douglas County, Oregon

17815

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 12 ins. diam., bears S. 16 1/2° E.,
44 lks. dist., mkd. 1/4 S13 BT.

A fir, 8 ins. diam., bears N. 33 1/2° W.,
8 lks. dist., mkd. 1/4 S12 BT.

S. 86° 58' W., beginning new measurement.

Descend over NW. slope.

28.20 Sleezer Creek, 6 lks. wide, course N. 5° W.; asc. over E. slope.

36.20 Dirt road, 15 lks. wide, bears N. 25° E., and S. 25° W.

40.55 The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S	R 6 W
S 11	S 12
S 14	S 13

1961

from which the remains of the original bearing trees

A fir stump, 32 ins. diam., bears N. 31° E.,
106 lks. dist., no marks visible.

A fir snag, 46 ins. diam., bears S. 33° W.,
14 lks. dist., fragmentary scribe marks
visible on opened blaze.

and bearing trees mkd. by Godfrey

A cedar, 29 ins. diam., bears N. 84 1/2° E.,
54 lks. dist., with healed double blaze.

A hemlock, 21 ins. diam., bears S. 42° E.,
110 lks. dist., with healed double blaze.

A hemlock, 21 ins. diam., bears N. 32° W.,
27 lks. dist., with healed double blaze.

and a bearing tree of which I have no record

A fir, 12 ins. diam., bears S. 78 1/2° W.,
46 lks. dist., with healed blaze.

GENERAL DESCRIPTION

The lands included in the foregoing resurvey are located in mountainous country about seven miles northwesterly from Drain, Oregon. The elevation ranges from about 1080 feet above sea level near the corner of sections 7, 12, 13, and 18, on the east boundary of the township, to about 1330 feet above sea level at the corner of sections 11, 12, 13, and 14.