

County Surveyor's Record, Douglas County, Oregon

17819

T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

The mean magnetic declination is 19° 15' E.

Dependent Resurvey of a Portion of the East Boundary,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by William Thiel in 1877,
the survey by William Thiel in 1891-92, and
the resurvey by Thomas A. Tillman in 1951-52)

Beginning at the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., perpetuated and recorded by Ronald E. Stuntzner, Registered Professional Engineer, No. 6245, in 1983, determined from the remaining original bearing trees

A cedar, 82 ins. diam., bears S. 55° E.,
30 lks. dist., with healed blaze.

A hemlock, 45 ins. diam., bears N. 48° W.,
26 lks. dist., with healed blaze.

and bearing trees mkd. by Tillman

A hemlock, 55 ins. diam., bears N. 53° E.,
176 lks. dist., with healed blaze.

A maple, 60 ins. diam., bears S. 33° W.,
90 lks. dist., with healed blaze.
(Record, S. 35 3/4° W., 94 lks.)

and a reference monument by Stuntzner

An iron rod, 5/8 in. diam., firmly set, projecting
3 1/2 ft. above ground, bears S. 2° E., 9 lks.
dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S	
R 10 W	R 9 W
S 25	S 30
S 36	S 31
1983	

N. 0° 10' E., bet. secs. 25 and 30, marking and blazing the true line.

Descend over NW slope, through heavy timber and dense undergrowth.

- 0.65 Ravine, drains W.; asc. over SW. slope.
 - 2.20 Spur, slopes W.; desc. over NW. slope.
 - 6.85 Ravine, drains S. 70° W.; asc. over SW. slope.
 - 18.60 Spur, slopes W.; desc. over NW. slope.
 - 19.64 Point for the S 1/16 sec. cor. of secs. 25 and 30.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.