

# County Surveyor's Record, Douglas County, Oregon

17820

Dependent Resurvey, Portion of the East Boundary,  
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

S 1/16  
S 25 | S 30  
1983

from which

A fir, 69 ins. diam., bears S. 81 1/2° E.,  
51 1/2 lks. dist., mkd. S 1/16 S30 BT.

A cedar, 56 ins. diam., bears S. 26 3/4° W.,  
27 lks. dist., mkd. S 1/16 S25 BT.

Descend over NW. slope.

20.10 Ravine, drains W.; asc. over SW. slope.

23.40 Ravine, drains S. 20° W.; asc. over SE. slope.

34.90 Gravelled road, 20 lks. wide, bears N. 70° E. and  
S. 80° W.

35.55 Spur, slopes S. 50° W.; desc. over NW. slope.

38.00 Same gravelled road, 20 lks. wide, bears N. 15° W. and  
S. 10° W., in curve; asc. over SW. slope.

39.28 The 1/4 sec. cor. of secs. 25 and 30, monumented with an  
iron post, 1 in. diam., firmly set, projecting 18 ins.  
above ground, with brass cap mkd.

1/4  
S 25 | S 30  
1951

from which the remaining bearing tree mkd. by Tillman

A fir, 16 ins. diam., bears S. 36° E., 32 lks.  
dist., with scribe marks 1/4 S30 BT visible  
on open blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 18 ins. diam., bears N. 24° W., 62 lks.  
dist., with scribe marks 1/4 S25 BT visible  
on open blaze.

Land, mountainous.

Soil, rocky and sandy loam.

Timber, fir, hemlock, cedar, alder, and maple; under-  
growth, vine maple, huckleberry, salmonberry, arrowwood,  
salal, Oregon grape, and ferns.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 20 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by John W. Meldrum in 1866-67,  
the survey by William H. Byars in 1874,  
the survey by William Thiel in 1877,  
the resurvey by Nathaniel Martin in 1892-94, and  
the resurvey by Thomas A. Tillman in 1951-52)

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy.  
of the township.