

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17821**
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	West, bet. secs. 25 and 36, marking and blazing the true line.
	Descend over NW. slope, through heavy timber and dense undergrowth.
3.00	Creek, 1 lk. wide, course S. 30° W.; asc. over SE. slope.
9.15	Spur, slopes S.; desc. over broken SW. slope.
18.25	Point for the E 1/16 sec. cor. of secs. 25 and 36. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$E \frac{1}{16} \begin{array}{l} S \ 25 \\ S \ 36 \end{array}$ 1983
	from which
	A fir, 25 ins. diam., bears S. 31 1/2° E., 26 lks. dist., mkd. E 1/16 S36 BT.
	A fir, 22 ins. diam., bears N. 23° W., 43 lks. dist., mkd. E 1/16 S25 BT.
	Descend over SW. slope.
18.90	Ravine, drains S. 5° E.; asc. over SE. slope.
22.05	Spur, slopes S. 30° W.; desc. over NW. slope.
25.75	Creek, 4 lks. wide, course S. 40° W.; asc. over SE. slope.
35.65	Spur, slopes S.; desc. over SW. slope.
36.50	The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.
	$1/4 \begin{array}{l} S \ 25 \\ S \ 36 \end{array}$ 1951
	from which bearing trees mkd. by Tillman
	A fir, 34 ins. diam., bears N. 63° E., 32 lks. dist., with healed blaze.
	A fir, 31 ins. diam., bears S. 80° E., 26 lks. dist., with healed blaze. (Record, 28 lks.)
	Land, mountainous. Soil, rocky and sandy loam Timber, fir, cedar, hemlock, maple, and chinquapin; undergrowth, huckleberry, salmonberry, rhododendron, salal, Oregon grape, vine maple, and ferns.