

# County Surveyor's Record, Douglas County, Oregon

**17822**

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 20 S., R. 10 W., Willamette Meridian, Oregon

**CHAINS**

From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 20 S	R 10 W
S 34	S 35
T 21 S	R 10 W
S 2	

1951

from which a bearing treemkd. by Martin

A fir, 75 ins. diam., bears S. 36 1/2° E.,  
388 lks. dist., with old axe marks visible  
(Record and to face, 381 lks.)

and bearing trees mkd. by Mensch and Collier

A fir, 45 ins. diam., bears N. 26° E., 117 lks.  
dist., with healed blaze.

A fir, 39 ins. diam., bears N. 8° W., 184 lks.  
dist., with healed blaze.

N. 1° 40' E., bet. secs. 34 and 35.

Descend over NE. slope through moderate timber and dense undergrowth.

13.90 Dailey Creek, 8 lks. wide, course N. 40° W.; asc. over SW. slope.

16.55 Gravelled road, 20 lks. wide, bears N. 15° W. and S. 20° E., in curve.

18.30 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set an ironpost, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16	
S 34	S 35
1983	

from which

An alder, 12 ins. diam., bears N. 53° E., 42 lks.  
dist., mkd. S 1/16 S35 BT.

A fir, 21 ins. diam., bears S. 20° W., 195 1/2 lks.  
dist., mkd. S 1/16 S34 BT.

The corner is located on edge of a vertical cut bank.

Ascend approximately 10 ft. over W. slope.

18.50 Top of ascent, slopes W.; desc. over NW. slope, changing to N. slope.

26.80 Gravelled road, 20 lks. wide, bears N. 65° E. and S. 65° W.

29.50 Leave timber, edge bears N. 80° E. and S. 80° W.; enter field.