

County Surveyor's Record, Douglas County, Oregon

17823

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS


33.19

The meander cor. of secs. 34 and 35, on the left bank of the Smith River, determined from the remaining bearing tree mkd. by Tillman

A fir, 42 ins. diam., bears S. 23 1/4° W., 180 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 25° E., 80 lks. dist., with brass cap mkd. MC S35 RM 1983 and an arrow pointing to the corner.

N. 1° 55' E., beginning new measurement.

Descend over sandy bank of river.

0.45

Left bank of Smith River, bears N. 60° E. and S. 60° W., course S. 60° W., thence across river.

1.365

The meander cor. of secs. 34 and 35, on the right bank of Smith River, determined from bearing trees mkd. by Tillman

A fir, 37 ins. diam., bears N. 61 1/4° E., 146 lks. dist., with healed blaze.

A fir, 31 ins. diam., bears N. 83° W., 183 lks. dist., with healed blaze.

The corner is located on the right bank of Smith River, bears N. 60° E. and S. 60° W., where it is impracticable to establish a permanent monument.

N. 1° 41' E., beginning new measurement.

Ascend over S. slope through heavy timber and moderate undergrowth.

0.60

Point selected for the witness cor. to the meander cor. of secs. 34 and 35, on the right bank of Smith River.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

