

County Surveyor's Record, Douglas County, Oregon

17824

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 11 ins. diam., bears N. 23 1/2° E.,
82 lks. dist., mkd. X BT.

An alder, 12 ins. diam., bears N. 84° W.,
39 lks. dist., mkd. X BT.

Ascend over S. slope.

1.75 Smith River Road, asphalt surface, 35 lks. wide, bears
N. 80° E. and S. 75° W.

2.05 Point for the 1/4 sec. cor. of secs. 34 and 35, determined
by the irregular boundary method; there is no remaining
evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in
the ground, with brass cap mkd.

*FD OK PER
BAKER 3-11-87
C.S. 65/50*

T 20 S R 10 W
 1/4
 |
 S 34 S 35
 |
 1983

from which

A fir, 8 ins. diam., bears N. 71 1/2° E.,
111 lks. dist., mkd. 1/4 S35 BT.

A fir, 10 ins. diam., bears N. 80 3/4° W.,
54 lks. dist., mkd. 1/4 S34 BT.

Set a steel fence, 5 1/2 ft. long, alongside iron post.

From this point, a corner established by person(s)
unknown, bears N. 39° 53' W., 0.254 chs. dist., monu-
mented with an iron pipe, 1 in. diam., firmly set,
projecting 12 ins. above ground.

N. 0° 12' E., beginning new measurement.

Ascend over steep S. slope, through heavy timber and
dense undergrowth.

3.95 Spur, slopes S. 55° E.; asc. over SE. slope, changing to
SW. slope.

19.91 Point for the N 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

N 1/16
 |
 S 34 S 35
 |
 1983

from which

A fir, 31 ins. diam., bears S. 70 1/2° E., 25 lks.
dist., mkd. N 1/16 S35 BT.

A fir, 15 ins. diam., bears S. 49° W., 25 lks.
dist., mkd. N 1/16 S34 BT.