


County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

17827

CHAINS

19.12 Point for the center S 1/16 sec. cor. of sec. 25.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1983

from which

A cedar, 60 ins. diam., bears N. 58 1/2° E.,
53 lks. dist., mkd. CS 1/16 S25 BT.

A fir, 55 ins. diam., bears S. 52 1/2° W.,
112 lks. dist., mkd. CS 1/16 S25 BT.

Descend over NW. slope.

19.95 Ravine, drains N. 80° W.; asc. over broken W. slope.


21.50 Spur, slopes W.; desc. over broken NW. slope.

29.65 Leave timber, edge bears N. 15° E. and W.; enter logged area.

32.05 Creek, 3 lks. wide, course S. 35° W.; asc. over broken SE. slope.

38.24 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1983

from which

A fir, 4 ins. diam., bears N. 30° E., 54 1/2 lks.
dist., mkd. X BT.

A fir, 20 ins. diam., bears S. 59° W., 169 lks.
dist., mkd. C 1/4 S25 BT.

Ascend over SE. slope, changing to broken S. slope.

60.60 Gravelled road, 20 lks. wide, bears N. 60° E. and S. 70° W. Leave logged area, edge bears same; enter timber.

61.25 Ridge, bears E. and W.; desc. over NE. slope.

67.80 Ravine, drains N. 45° W.; asc. over SW. slope.

72.30 Spur, slopes N. 45° W.; desc. over NE. slope.

76.75 The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.