

County Surveyor's Record, Douglas County, Oregon

17828

Subdivision of Section 25,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	$1/4 \begin{array}{l} S \ 24 \\ S \ 25 \end{array}$ <p>1951</p> <p>from which the remains of bearing trees mkd. by Tillman</p> <p style="padding-left: 40px;">A hemlock, 24 ins. diam., bears S. 55° E., 42 1/2 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 66 ins. diam., bears N. 73° W., 64 lks. dist., with healed blaze.</p> <p>No other suitable trees available.</p>
	<p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 88° 25' W., on the E. and W. center line of sec. 25.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p>
0.50	Gravelled road, 20 lks. wide, bears N. 50° W. and S. 25° E., in curve.
10.75	Ravine, drains S.; asc. over SE. slope.
17.30	Spur, slopes S. 35° W.; desc. over NW. slope.
18.845	Point for the center E 1/16 sec. cor. of sec. 25.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $C \begin{array}{l} E \ 1/16 \\ S \ 25 \end{array} C$ <p>1983</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 44 ins. diam., bears N. 50 1/4° E., 116 lks. dist., mkd. CE 1/16 S25 BT.</p> <p style="padding-left: 40px;">A fir, 72 ins. diam., bears S. 76 1/4° W., 159 lks. dist., mkd. CE 1/16 S25 BT.</p> <p>Descend over NW. slope.</p>
26.95	Creek, 1 lk. wide, course S. 55° W.; asc. over SE. slope.
31.55	Spur, slopes S. 30° W.; desc. over SW. slope.
33.25	Leave timber, edge bears N. and S.; enter logged area.
34.60	Creek, 3 lks. wide, course S. 10° W.; asc. over SE. slope.
37.69	The center 1/4 sec. cor. of sec. 25.
	Ascend over broken SE. slope.
49.95	Gravelled road, 20 lks. wide, bears N. 10° E. and S. 10° E.