

County Surveyor's Record, Douglas County, Oregon

17830

Subdivision of Section 25,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	From the S 1/16 sec. cor. of sec. 25 and 30, on the E. bdy. of the Tp.
	S. 89° 12' W., on the E. and W. centerline of the SE 1/4 of sec. 25.
	Descend over NW. slope, through heavy timber and dense undergrowth.
0.75	Ravine, drains S. 10° W.; asc. over SE. slope.
7.50	Spur, slopes S. 20° W.; desc. over NE. slope.
17.90	Creek, 4 lks. wide, course S. 20° W.; asc. over SE. slope.
18.555	The SE 1/16 sec. cor. of sec. 25.
	Ascend over SE. slope.
29.65	Saddle in spur, bears N. 30° E. and S. 30° W.; desc. over NW. slope.
37.10	The center S 1/16 sec. cor. of sec. 25.

Subdivision of Section 34,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

	From the 1/4 sec. cor. of sec. 34 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<u>1/4 S 34</u> 1951
	from which a bearing tree mkd. by Mensch and Collier
	A fir, 31 ins. diam., bears N. 5° W., 66 lks. dist., with healed blaze.
	and a bearing tree mkd. by Tillman
	A fir, 35 ins. diam., bears N. 11° E., 97 lks. dist., with healed blaze. (Record, N. 8 1/2° E.)
	N. 0° 38' E., on the N. and S. center line of sec. 34.
	Descend over NE. slope, through heavy timber and dense undergrowth.
0.30	Ravine, drains E.; asc. over SE. slope.
1.65	Spur, slopes N. 65° E.; desc. over broken NE. slope.
19.665	Point for the center S 1/16 sec. cor. of sec. 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C S 1/16 S 34 C 1983