

County Surveyor's Record, Douglas County, Oregon

17831

Subdivision of Section 34,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 12 ins. diam., bears S. 6 1/4° E., 73 lks.
dist., mkd. CS 1/16 S34 BT.

A fir, 7 ins. diam., bears N. 85 1/4° W., 315 lks.
dist., mkd. CS 1/16 S34 BT.

Continue over nearly level land.

20.85 Left bank of Smith River, bears N. 75° E. and N. 75° W.,
course N. 75° W.; thence across river.

22.90 Right bank of Smith River, bears E. and W.; asc. over
nearly level land, across E. edge of field.

25.10 Barbed wire fence, extends N. 75° W. and S. 80° E.

25.70 Smith River Road, asphalt surface, 35 lks. wide, bears
N. 70° W. and E., in curve; asc. over S. slope, changing
to SW. slope. Also, enter heavy timber and dense under-
growth.

37.10 Spur, slopes W.; desc. over NW. slope.

39.15 Creek, 1 lk. wide, course W.; asc. over SW. slope.

39.33 Point for the center 1/4 sec. cor. of sec. 34, at intersec-
tion with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 20 S R 10 W
C 1/4 S 34

1983

from which

A fir, 15 ins. diam., bears S. 32 3/4° W.,
101 lks. dist., mkd. C 1/4 S34 BT.

A fir, 37 ins. diam., bears N. 48 1/4° W.,
152 1/2 lks. dist., mkd. C 1/4 C34 BT.

Ascend over broken SW slope.

48.05 Spur, slopes S. 75° W.; desc. over NW. slope.

52.00 Creek, 1 lk. wide, course S. 50° W.; asc. over SE. slope,
changing to SW. slope.

59.525 Point for the center N 1/16 sec. cor. of sec. 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

C
|
N 1/16 | S 34
|
C

1983

from which