

County Surveyor's Record, Douglas County, Oregon

17832

Subdivision of Section 34,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 9 ins. diam., bears N. 60 1/4° E., 49 1/2 lks. dist., mkd. CN 1/16 S34 BT.</p> <p>A fir, 18 ins. diam., bears N. 58 1/4° W., 61 lks. dist., mkd. CN 1/16 S34 BT.</p> <p>Ascend over SW. slope.</p>
60.60	Spur, slopes W.; desc. over NW. slope.
62.05	Ravine, drains N. 70° W.; asc. over broken SW. slope.
73.00	Ridge, bears N. 60° W. and S. 60° E.; desc. over NE. slope.
79.72	The 1/4 sec. cor. of secs. 27 and 34.
	<p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89° 38' W., on the E. and W. center line of sec. 34.</p> <p>Ascend along S. slope, through heavy timber and dense undergrowth.</p>
2.55	Top of ascent, slopes S.; desc. over W. slope.
4.00	Creek, 2 lks. wide, course S. 20° W.; asc. over SE. slope.
13.20	Spur, slopes S.; desc. over SW. slope.
16.85	Creek, 2 lks. wide, course S. 20° E.; asc. over SE. slope.
19.90	Point for the center E 1/16 sec. cor. of sec. 34
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E\ 1/16}{1983}$ C</p> <p>from which</p> <p>A fir, 9 ins. diam., bears S. 17° W., 29 1/2 lks. dist., mkd. CE 1/16 S34 BT.</p> <p>A fir, 12 ins. diam., bears N. 45 1/2° W., 36 lks. dist., mkd. CE 1/16 S34 BT.</p> <p>Ascend over SE. slope.</p>
25.60	Spur, slopes S. 50° W.; desc. over SW. slope, changing to NW. slope.
35.60	Creek, 1 lk. wide, course S. 80° W.; desc. over SW. slope.
39.80	The center 1/4 sec. cor. of sec. 34.
	Descend over SW. slope.
51.50	Smith River Road, asphalt surface, 30 lks. wide, bears N. 15° W. and S. 15° E.; also leave timber, edge bears same.