

County Surveyor's Record, Douglas County, Oregon

17834

Subdivision of Section 34,
T. 20 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<div style="display: flex; justify-content: center; align-items: center; gap: 20px;"> <div style="text-align: center;">WC ↓ 1983</div> <div style="text-align: center;">NE 1/16 S 34</div> </div>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 56 ins. diam., bears N. 10° E., 26 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 23 ins. diam., bears S. 71 1/2° W., 35 lks. dist., mkd. X BT.</p> <p>Ascend over S. slope.</p>
22.20	Ridge, bears N. 80° E. and N. 80° W.; desc. over NE. slope, changing to broken NW. slope, also leave timber, edge bears N. 5° W. and SE., enter logged area.
40.10	The E 1/16 sec. cor. of secs. 27 and 34.
	<p>From the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>N. 89° 14' W., on the E. and W. center line of the NE 1/4 of sec. 34.</p> <p>Descend over SW. slope, along N. edge of timber and dense undergrowth.</p>
2.55	Ravine, drains S.; asc. over SE. slope.
18.15	Spur, slopes S. 35° E.; desc. over SW. slope.
19.83	True point for the NE 1/16 sec. cor. of sec. 34.
	Ascend over SE. slope.
21.75	Spur, slopes S. 35° W.; desc. over NW. slope.
30.10	Creek, 1 lk. wide, course S. 80° W.; desc. over SW. slope.
33.65	Ravine, drains S. 30° W.; asc. over SE. slope.
37.10	Spur, slopes S.; desc. over SW. slope.
39.66	The center N 1/16 sec. cor. of sec. 34.
	<p>From the S 1/16 sec. cor. of secs. 34 and 35.</p> <p>S. 88° 22' W., on the E. and W. center line of the SE 1/4 of sec. 34.</p> <p>Descend over W. slope, through heavy timber and dense undergrowth.</p>
0.45	Gravelled road, 20 lks. wide, bears N. 10° W. and S. 15° E.
2.35	Dailey Creek, 6 lks. wide, course N. 5° E.; asc. over NE. slope.
7.75	Spur, slopes N.; desc. over gentle NW. slope.
14.80	Creek, 1 lk. wide, course N. 55° W.; asc. over NE. slope.