

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

17839

**CHAINS**

19.99

The witness cor. to the E 1/16 sec. cor. of secs. 21 and 28, monumented with an iron post, 2 1/2 ins, diam., firmly set, with top 24 ins. below surface, with brass cap mkd.

E 1/16  $\begin{matrix} \text{S } 21 \\ \text{S } 28 \end{matrix}$  WC  
1965

from which the remains of the bearing trees mkd. by Jelley

A fir, 24 ins. diam., bears N. 79° E.,  
47 lks. dist., with healed blaze.

A fir snag, 12 ins. diam., bears S. 20° E.,  
31 lks. dist., with scribe marks BT visible  
on partially healed blaze.

and a bearing tree mkd. by Vernon R. Tracy, Deputy  
County Surveyor, in 1973

A. fir, 15 ins. diam., bears S. 31° W.,  
110 lks. dist., with healed double blaze.

---

Subdivision of Section 21,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

---

From the 1/4 sec. cor. of secs. 21 and 28, monumented  
with an iron post, 1 1/4 ins. diam., firmly set,  
projecting 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S  
    S 21  
1/4 S 28  
R 7 W  
BLM 1965  
1965

from which bearing trees mkd. by Tracy

A fir, 28 ins. diam., bears N. 55° E.,  
10 lks. dist., with healed double blaze.

A fir, 25 ins. diam., bears S. 34° W.,  
14 lks. dist., with healed double blaze.

N. 0° 19' E., on the N. and S. center line of sec. 21.

Ascend over SE. slope, through heavy timber and dense  
undergrowth.

5.75

Spur, slopes N. 80° E.; desc. over NE. slope.

23.25

West Eork Buck Creek, 5 lks. wide, course S. 85° E.;  
asc. over SE. slope, changing to E. slope.

39.10

Spur, slopes N. 75° E.; desc. along NE. slope

39.33

Point for the center 1/4 sec. cor. of sec. 21, at  
intersection with the E. and W. center line.