

County Surveyor's Record, Douglas County, Oregon

17840

Subdivision of Section 21,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 1 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
C 1/4
S 21
1983

from which

A fir, 14 ins. diam., bears S. 27 1/2° E.,
22 1/2 lks. dist., mkd. C1/4 S21 BT.

A fir, 4 ins. diam., bears N. 63 1/2° W.,
28 1/2 lks. dist., mkd. X BT.

Descend over NE. slope.

43.25 Buck Creek, 4 lks. wide, course S. 65° E.; asc. over SE. slope.

53.35 Gravelled road, 15 lks. wide, bears N. 75° W. and S. 65° E.

68.75 Ridge, bears N. 45° W. and S. 45° E.; desc. over N. slope.

69.25 Gravelled road, 15 lks. wide, bears N. 35° W. and S. 35° E.

78.69 The 1/4 sec. cor. of secs. 16 and 21, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 16
1/4 S 21
R 7 W
1965

from which the remains of an original bearing tree

A pine snag, 38 ins. diam., bears N. 31° E.,
34 lks. dist., no marks visible.

and a bearing tree mkd. by Tracy

A fir snag, 14 ins. diam., bears S. 89° E., 17 lks. dist., with scribe marks 1/4 S CS visible on partially healed blaze. (Record, N. 89° E.)

and new bearing trees

A fir, 4 ins. diam., bears S. 2 1/2° W.,
51 lks. dist., mkd. X BT.

A fir, 10 ins. diam., bears N. 3 1/2° W.,
58 lks. dist., mkd. 1/4 S16 BT.

From this point, United States Geological Survey triangulation station "BUCK MTN. 1942", bears N. 23° 42' E., 107.62 chs. dist., monumented with a bronze disk, 3 ins. diam., set in concrete, with top mkd. BUCK MTN 1942.