

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

17841

CHAINS

From the 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 30 S R 7 W
1/4
S 21 | S 22
1965

from which the remains of bearing trees mkd. by Jelley

A fir stump, 40 ins. diam., bears S. 45° E.,
25 lks. dist., no marks visible.

A fir, 38 ins. diam., bears S. 58° W.,
77 lks. dist., with healed blaze.

and a new bearing tree

A white fir, 14 ins. diam., bears N. 53 1/2° W.,
43 lks. dist., mkd. 1/4 S 21 BT.

No suitable tree available in sec. 22.

S. 88° 37' W., on the E. and W. center line of sec. 21,

Ascend over NE slope, through scattering timber and dense undergrowth.

13.20 Ridge, bears N. 25° W. and S. 25° E.; desc. over NW. slope; also gravelled road, 15 lks. wide, bears N. 25° W. and S. 35° E.

19.76 Point for the center E 1/16 sec. cor. of sec. 21.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16
C S 21 C
1983

from which

A fir, 22 ins. diam., bears S. 21 1/2° E.,
36 lks. dist., mkd. CE 1/16 S21 BT.

A fir, 7 ins. diam., bears N. 12° W.,
30 lks. dist., mkd. CE 1/16 S 21 BT.

Descend over NW. slope.

23.75 Slope changes; desc. over SW. slope

35.80 Buck Creek, 4 lks. wide, course S. 45° E.; asc. over NE. slope.

39.52 The center 1/4 sec. cor. of sec. 21.

60.20 Dirt road, 15 lks. wide, bears N. 35° W. and S. 35° W., in a curve.

60.70 Dirt road, 15 lks. wide, bears N. 55° W. and S. 45° E.

79.38 The 1/4 sec. cor. of secs. 20 and 21, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.