

County Surveyor's Record, Douglas County, Oregon

17847

Dependent Resurvey, Portion of the South Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Corner tree, a decayed hemlock stump, size indeterminate, no marks visible, from which the remains of bearing trees and a reference monument mkd. by Templin

An iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, bears North, 1½ lks. dist., mkd. WC on N. side.

A cedar stump, 27 ins. diam., bears S. 31½° E., 55½ lks, dist. with scribe marks S2 BT RE 3024 visible on decayed blaze.

A grand fir, 22 ins. diam., bears N. 23¼° W., 62 lks. dist., with healed blaze.

and a reference monument and a bearing tree mkd. by Powell

An iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, bears north, 1½ lks. dist., alongside the iron pipe, with brass cap mkd. COUNTY SURVEYORS OFFICE T30 S R3W ¼ S35 T31S 1965.

A grand fir, 11 ins. diam., bears N. 56½° E., 38 lks. dist., with healed blaze.

N. 89° 49' W., beginning new measurement.

Ascend over broken NE. slope.

5.90 Ridge, bears N. 20° W. and S. 20° E.; desc. over NW. slope.

7.285 From this point, the original closing cor. of secs. 2 and 3, T. 31 S., R. 3 W., bears North, 0.135 chs. dist., perpetuated and recorded by John H. Markam, Jr., Registered Engineer No. 2880, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1965, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 3 W
CC

S 3 | S 2
T 31 S
1965

from which the remaining original bearing trees

a fir, 45 ins. diam., bears n. 18° E., 43 lks. dist., with healed blaze.

A madrone, 33 ins. diam., bears S. 28 3/4° W., 24 lks. dist., no marks visible.
(record, S. 36¼° W.)

and bearing trees mkd. by Markam

A madrone, 16 ins. diam., bears N. 59½° E., 61 lks. dist., with scribe marks T30S R3W S35 BT visible on bark blaze.