

County Surveyor's Record, Douglas County, Oregon

17849

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Nathaniel Ford, in 1854,
the resurvey by Dennis Hathorn, in 1857, and
the resurvey by William Thiel, in 1889)

From the cor. of secs. 19 and 30 only, perpetuated and
recorded by Ben B. Irving, Deputy County Surveyor, in
1948, monumented with an iron pipe, 1 1/4 ins. diam.,
firmly set, projecting 2 ins. above ground, from which
the remaining original bearing trees

A madrone, 20 ins. diam., bears N. 40° E.,
33 lks. dist., with partially healed blaze,
no marks visible.

A madrone, 38 ins. diam., bears S. 45° E.,
44 lks. dist., with healed blaze.
(Record, 40 lks.)

A madrone, 18 ins. diam., bears N. 50° W.,
19 lks. dist., with open decayed blaze.

and a bearing tree mkd. by Irving

A chinquapin, 14 ins. diam., bears N. 32° W.,
26 lks. dist., with scribe marks T30S R4W S24
CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, directly over the iron pipe, with brass
cap mkd.

T 30 S
R 4 W R 3 W
S 24 | S 19
 | S 30
 1983

*FND OK R. BROWN
8/92 M 115-56*

N. 0° 05' E., on the W. bdy. of sec. 19, marking and
blazing the true line.

Descend over NW. slope, through heavy timber and dense
undergrowth.

1.95 Ravine, drains S. 70° W.; asc. over SW. slope.

2.60 3 wire power transmission line, bears N. 70° W., and
S. 70° E.

5.90 Spur, slopes W.; desc. over NW. slope.

19.49 Point for the S 1/16 sec. cor. of sec. 19 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

S 1/16
S 19

1983

from which