

# County Surveyor's Record, Douglas County, Oregon

17850

Dependent Resurvey of a Portion of the West Boundary  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

38.98

An oak, 20 ins. diam., bears N. 64 1/4° E.,  
183 lks. dist., mkd. S 1/16 S19 BT.

A fir, 6 ins. diam., bears S. 72 1/4° E.,  
280 lks. dist., mkd. S 1/16 S19 BT.

Descend over NW. slope.

Point for the 1/4 sec. cor. of sec. 19 only, determined  
by the method of irregular boundaries; there is no  
remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

*Find OK 8/92  
R. Brown M. 115-56*

T 30 S	
R 4 W	R 3 W
	1/4
	S 19

1983

from which

An oak, 44 ins. diam., bears N. 6° E.,  
467 lks. dist., mkd. 1/4 S19 BT.

An oak, 17 ins. diam., bears S. 54 1/2° E.,  
7 1/2 lks. dist., mkd. 1/4 S29 BT.

From this point, a cor. established and recorded by  
George J. Wenderoth, Registered Land Surveyor, No. 5,  
in 1950-51, bears S. 82° 20' E., 1.087 chs. dist.,  
determined from the remaining bearing tree mkd. by  
Wenderoth.

An oak, 17 ins. diam., bears N. 84 1/2° W.,  
101 lks. dist., with healed blaze.

N. 2° 54' E., beginning new measurement.

Descend over NW. slope.

8.90

Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

11.50

Bland Branch, 10 lks. wide, course S. 60° W.; asc. over  
broken SE. slope.

11.85

From this point, a cor. established and recorded by  
George J. Wenderoth, Registered Land Surveyor, No. 5,  
bears East, 0.710 chs. dist., monumented with an axle,  
1 1/4 ins. diam., firmly set, flush with ground, from  
which bearing trees mkd. by Wenderoth

An oak, 14 ins. diam., bears S. 47° W.,  
25 lks. dist., with healed blaze.

An oak, 12 ins. diam., bears N. 23 1/2° W.,  
39 lks. dist., with healed blaze.