

County Surveyor's Record, Douglas County, Oregon

17852 Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

land, mountainous.
Soil, clay loam.
Timber, yew, oak, fir, cedar, willow, alder, ash, pine,
madrone, and chinquapin; undergrowth, poison oak,
Oregon grape, salal, arrowwood, hazel, blackberry,
thimbleberry, salmonberry, huckleberry, ferns, and
young timber.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, in 1857, and
the survey by William M. Bushey, in 1893)

From the cor. of secs. 35 and 36 only, on the S.bdy.
of the Tp.

N. 0° 39' W., bet. secs. 35 and 36, marking and blazing
the true line.

Ascend over SW. slope, through heavy timber and dense
undergrowth.

- | | |
|-------|--|
| 0.40 | Spur, slopes N. 60° W.; desc. over NW. slope, changing
to NE. slope. |
| 2.55 | Gravelled road, 20 lks. wide, bears N. 80° E. and
S. 80° W. |
| 16.35 | Creek, 3 lks. wide, course S. 60° W.; asc. over
SE. slope. |
| 24.30 | Gravelled road, 20 lks. wide, bears N. 55° E. and
S. 55° W. |
| 31.73 | The 1/4 sec. cor. of secs. 35 and 36, perpetuated and
recorded by A. Victor Cangie, Deputy County Surveyor,
in 1976, monumented with an iron post, 1 1/4 ins. diam.,
firmly set, projecting 8 ins. above ground, with brass
cap mkd. |

DOUGLAS COUNTY SURVEYOR
T 30 S R 3 W

S 35 | S 36
1/4
1976

from which the original bearing trees

A fir, 34 ins. diam., bears S. 66 3/4° E.,
23 lks. dist., with opened blaze, no marks
visible.

A pine, 46 ins. diam., bears N. 63 1/2° W.,
56 lks. dist., with scribe marks 1/4 visible
on opened blaze.

N. 0° 02' E., beginning new measurement.

Ascend over SE. slope.