

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

17853

**CHAINS**

4.25

Spur, slopes S. 60° W.; desc. over broken NW. slope.

39.19

The cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S	
S 26	S 25
S 35	S 36
T 3 W	

1963

from which bearing trees mkd. by Bushey

A fir, 39 ins. diam., bears S. 3 3/4° E.,  
44 lks. dist., with healed blaze.  
(Record, 49 1/2 lks.)

A fir, 31 ins. diam., bears S. 21° W.,  
54 lks. dist., with healed double blaze.

A fir, 40 ins. diam., bears N. 85° W.,  
73 lks. dist., with healed double blaze.

and a bearing tree mkd. by Byron

A fir, 38 ins. diam., bears N. 71 3/4° E.,  
81 lks. dist., with healed double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, oak, maple, fir, hemlock, yew, alder, madrone,  
cedar, pine, willow; undergrowth, poison oak,  
arrowwood, hazel, salal, Oregon grape, vine maple,  
manzanita, ferns, ceanothus, and young timber.

From the cor. of secs. 34 and 35 only, on the S. bdy.  
of the Tp.

N. 0° 02' W., bet. secs. 34 and 35.

Descend over broken N. slope, through heavy timber and  
dense undergrowth.

19.00

Gravelled road, 25 lks. wide, bears N. 80° W., and  
S. 80° E.

19.75

Creek, 5 lks. wide, course N. 80° W.; asc. over broken  
SW. slope.

25.15

Gravelled road, 25 lks. wide, bears N. 30° W. and  
S. 30° E.

30.16

The 1/4 sec. cor. of secs. 34 and 35, perpetuated and recorded by Richard L. Templin, Jr., Registered Logging Engineer, No. 3024, in 1954, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees