

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

17855

CHAINS

A grand fir, 14 ins. diam., bears S. 12 1/2° E.,
23 lks. dist., mkd. N 1/16 S35 BT.

A fir, 5 ins. diam., bears S. 57 1/2° W.,
17 lks. dist., mkd. X BT.

Reset iron pipe alongside iron post.

N. 1° 13' W., beginning a new measurement.

Descend over broken NE. slope.

15.50 Left bank of South Umpqua River, bears N. 65° E.,
S. 65° W., course S. 65° W.

16.35 Right bank of South Umpqua River, bears N. 65° E. and
S. 65° W.; asc. over SE. slope.

17.80 3 wire power service line, bears E. and W.

20.25 The cor. of secs. 26, 27, 34, and 35, perpetuated by
Frank Cain, Deputy County Surveyor, and recorded by
Floyd C. Frear, County Surveyor, in 1920, monumented
with a flanged axle, 1 1/4 ins. diam., firmly set, top
2 ins. below ground, alongside a stone, 10 x 10 x 6
ins., firmly set, top 4 ins. below ground, mkd. X on
top, from which remains of an original bearing tree

A decayed fir stump, 36 ins. diam., bears
S. 10° E., 150 lks. dist., with scribe
marks BT visible on opened blaze.

and bearing trees mkd. by Cain

A pine, 20 ins. diam., bears S. 83 3/4° E.,
132 lks. dist., with fragmentary scribe
marks visible on partially healed blaze.

An oak, 26 ins. diam., bears S. 5°W.,
42 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 30 ins.
in the ground, with brass cap mkd.

T 30 S	R 3 W
S 27	S 26
S 34	S 35

1983

FD OK BY
R. Quimby
CO. RD #1
5/95

from which a new bearing tree and bearing object

A cedar, 12 ins. diam., bears N. 47 1/2° E.,
159 lks. dist., mkd. T30S R3W S26 BT.

A power pole, bears N. 51 1/2° W., 125 lks.
dist., No. A 26.

Reset axle and deposit corner stone alongside iron post.

The corner is located 0.75 chs. south of State Highway
No. 42, paved, 50 lks. wide, bears N. 65° E. and
S. 65° W.