

County Surveyor's Record, Douglas County, Oregon

17856 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, yew, maple, oak, cedar, willow, alder, madrone, chinquapin, dogwood, cottonwood, and hemlock; undergrowth, blackberry, arrowood, Oregon grape, fern, ceanothus, thimbleberry, salal, wild rose, huckleberry, poison oak, vine maple, and manzanita.

40.65

From the cor. of secs. 25, 26, 35, and 36.

S. 89° 19' W., bet. secs. 26 and 35.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

The 1/4 sec. cor. of secs. 26 and 35, perpetuated and recorded by Richard L. Templin, Jr., Registered Engineer, No. 3024, in 1953, from original evidence no longer in existence, and further perpetuated and recorded by Donald L. McConnell, Registered Land Surveyor, No. 859, in 1979, monumented with an iron rod, 5/8 in. diam., firmly set inside an iron pipe, 1 1/2 ins. diam., firmly set, top is 6 ins. below surface of ground, with plastic cap mkd. McCONNELL RLS 859

from which bearing trees mkd. by Templin

An oak, 30 ins. diam., bears S. 88 1/2° E.,
581 lks. dist., with healed blaze.

An oak, 30 ins. diam., bears S. 27° E.,
808 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron rod and iron pipe, with brass cap mkd.

T 30 S R 3 W
1/4 $\frac{S 26}{S 35}$
1983

from which a new bearing tree

An oak, 32 ins. diam., bears N. 89 3/4° E.,
580 lks. dist., mkd. 1/4 S26 BT.

From this point, the Douglas County Surveyors Office horizontal control station "VIC AZI", 1975, bears N. 1° 31' E., 48.62 chs. dist., monumented with a brass tablet, 1 1/2 ins. diam., set in a concrete post, 6 ins. diam., firmly set, projecting 2 ins. above ground, with top mkd. Douglas County Surveyors Office VIC AZI -- 1975

N. 89° 39' W., beginning new measurement.

Descend slightly over nearly level pasture land.

8.95

Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.

36.20

Left bank of South Umpqua River, bears N. 55° E. and S. 50° W., course S. 50° W.