

# County Surveyor's Record, Douglas County, Oregon

17858      Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

39.59

From the 1/4 sec. cor. of secs. 19 and 30, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1927, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 30 S	R
1/4	S 19	3
	S 30	W

1963

from which the remains of an original bearing tree

A sawed fir stump, 44 ins. diam., bears  
S. 80° E., 39 lks. dist., with axe marks  
visible on bark.

and a bearing tree mkd. by Irving

A fir, 36 ins. diam., bears N. 54° E.,  
66 lks. dist., with healed blaze.

and a bearing tree mkd. by Byron

A fir, 21 ins. diam., bears S. 42° W.,  
23 lks. dist., with healed blaze.

---

S. 87° 18' W., beginning new measurement.

Ascend over SE. slope.

11.30

Spur, slopes S. 30° W.; desc. over broken NW. slope.

20.13

The W 1/16 sec. cor. of secs. 19 and 30, established and recorded by ARTHUR R. EVANS, Deputy County Surveyor, in 1948, and is accepted as the corner, monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Evans

A madrone root crown, size indeterminate, bears  
South, 28 lks. dist., no marks visible.

A madrone, 26 ins. diam., bears N. 18 1/2° W.,  
25 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	W 1/16	S 19
		S 30

1983

from which new bearing trees

A madrone, 7 ins. diam., bears S. 3 1/4° W.,  
29 lks. dist., mkd. W 1/16 S30 BT on bark.

A fir, 5 ins. diam., bears N. 2° W., 41 lks.  
dist., mkd. W 1/16 S19 BT.