

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

17859

CHAINS	
	<p>Reset iron pipe alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 87° 20' W., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
14.50	<p>3 wire power transmission line, bears N. 70° W. and S. 70° E.</p>
21.66	<p>The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay. Timber, pine, oak, madrone, fir, chinquapin, alder, yew, and cedar; undergrowth, poison oak, huckleberry, Oregon grape, salal, arrowwood, hazel, blackberry, salmonberry, and young timber.</p>
38.60	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 02' E., bet. secs. 19 and 20.</p> <p>Ascend over SW. slope, changing to SE. slope, through heavy timber and dense undergrowth.</p> <p>Ridge, bears N. 30° E. and S. 30° W.; desc. over NW. slope.</p>
39.66	<p>The 1/4 sec. cor. of secs. 19 and 20, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1950, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 3 ins. above ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 55 ins. diam., bears N. 30° W., 36 lks. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Wenderoth</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 26 3/4° E., 45 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A madrone snag, 14 ins. diam., bears S. 88 1/2° W., 53 lks. dist., with fragmentary scribe marks visible on open decayed double blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 78 3/4° W., 31 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p>