

County Surveyor's Record, Douglas County, Oregon

17860

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

17860

CHAINS

T 30 S R 3 W

$\frac{1}{4}$
 S 19 | S 20
 1983

N. 0° 01' E., beginning new measurement.

Descend over broken NW. slope.

19.93

Point for the N 1/16 sec. cor. of secs. 19 and 20.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with aluminum cap mkd.

N 1/16
 S 19 | S 20
 1983

from which

A fir, 9 ins. diam., bears N. 39 3/4° E.,
19 lks. dist., mkd. N 1/16 S20 BT.

A cedar, 10 ins. diam., bears N. 54° W.,
60 lks. dist., mkd. N 1/16 S19 BT.

Descend over NW. slope.

30.05

Lavadoire Creek, 8 lks. wide, course S. 50° W.; asc.
over SE. slope.

35.40

Spur, slopes S. 75° E.; desc. over NE. slope.

39.86

The cor. of secs. 17, 18, 19, and 20, perpetuated and
recorded by George J. Wenderoth, Registered Land
Surveyor, No. 5, in 1950, further perpetuated and
recorded by James W. Byron, Deputy County Surveyor, in
1963, and still further perpetuated and recorded by
Larry E. Monrean, Deputy County Surveyor, in 1976,
monumented with an iron post, 1 1/4 ins. diam., firmly
set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 3 W
 S 18 | S 17
 S 19 | S 20

1976

from which the remains of the original bearing trees

A maple, 20 ins. diam., bears N. 18° E.,
66 lks. dist., with healed blaze.

A root hole, bears S. 18° E., 14 lks. dist.,
with down fir alongside, 14 ins. diam.,
no marks visible.

A sawed fir stump, 37 ins. diam., bears
S. 78° W., 68 lks. dist., with scribe marks
BT visible on opened blaze.