

County Surveyor's Record, Douglas County, Oregon

17862 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 12 ins. diam., bears N. 75° E.,
19 lks. dist., mkd. E 1/16 S18 BT.

A fir, 17 ins. diam., bears S. 25 1/2° E.,
36 lks. dist., mkd. E 1/16 S19 BT.

Reset angle iron alongside iron post.

S. 85° 41' W., beginning new measurement.

Ascend over broken SE. slope.

19.93

The 1/4 sec. cor. of secs. 18 and 19, reestablished and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1950-51, and is accepted as the best available evidence of the position of the original corner, and perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an angle iron, 1 1/4 x 1/4 ins., firmly set, projecting 12 ins. above ground, from which the remains of bearing trees mkd. by Wenderoth

A fir, 25 ins. diam., bears S. 56° W.,
114 lks. dist., with healed blaze.

A sawed fir stump, 20 ins. diam., bears
N. 65° W., 112 lks. dist., with healed
blaze.

and bearing trees mkd. by Byron

A fir, 22 ins. diam., bears S. 58 1/2° W.,
64 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 25° W.,
28 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 3 W
1/4 $\frac{S 18}{S 19}$
1983

Reset angle iron alongside iron post.

The corner is located 2 lks. S. of barbed wire fence, extending E. and W.

From this point, the United States Geological Survey, Triangulation Station "BLAND MTN", 1953, bears N. 33° 56' W., 61.99 chs. dist., monumented with brass disk, 3 1/4 ins. diam., set in a boulder projecting 8 ins. above ground, with top mkd. U.S. Geological Survey 1953 Elevation Above Sea Level Bland Mtn Bench Mark + .

S. 86° 23' W., beginning new measurement.