

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

17863

CHAINS	
	Ascend over SE. slope.
2.60	Dirt road, 15 lks. wide, bears N. 20° E. and S. 40° W.
4.30	Spur, slopes S. 5° E.; desc. over broken SW. slope.
36.95	Bland Branch, 5 lks. wide, course S. 20° E.; asc. over SE. slope.
39.92	The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, yew, oak, maple, madrone, chinquapin, alder, cedar, and dogwood; undergrowth, blackberry, ferns, manzanita, Oregon grape, salal, poison oak, vine maple, huckleberry, salmonberry, and young timber.
	Subdivision of Section 19, T. 30 S., R. 3 W., Willamette Meridian, Oregon
	From the 1/4 sec. cor. of secs. 19 and 30.
	N. 0° 04' E., on the N. and S. center line of sec. 19, marking and blazing the true line.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
2.90	Creek, 2 lks. wide, course S. 20° E.; asc. over SW. slope.
12.00	Top of ascent, slopes S. 30° E.; desc. over NE. slope.
19.64	Point for the center S 1/16 sec. cor. of sec. 19.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	C S 1/16 S 19 C 1983
	from which
	A fir, 10 ins. diam., bears S. 47 1/2° E., 58 lks. dist., mkd. CS 1/16 S19 BT.
	A fir, 13 ins. diam., bears N. 20° W., 40 1/2 lks. dist., mkd. CS 1/16 S 19 BT.
	From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1950-51, bears S. 62° 34' E., 0.234 chs. dist., monumented with an angle iron, 1 1/2 x 1/4 ins., firmly set, projecting 8 ins. above ground, from which bearing tree mkd. by Wenderoth
	A fir, 26 ins. diam., bears N. 30° W., 53 lks. dist., with healed blaze.