

# County Surveyor's Record, Douglas County, Oregon

17864

Subdivision of Section 19,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	Descend over NE. slope.
23.75	Head of ravine, drains E.; asc. over broken SE. slope.
36.35	Top of ascent, slopes E.; desc. over NE. slope.
37.65	Head of ravine, drains S. 80° E.; asc. over SE. slope.
39.28	Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 30 S    R 3 W C 1/4 S 19  1983
	from which
	A cedar, 8 ins. diam., bears S. 3° W., 36 lks. dist., mkd. C 1/4 S19 BT.
	A fir, 6 ins. diam., bears N. 2° W., 28 1/2 lks. dist., mkd. C 1/4 S19 BT.
	From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1950-51, bears S. 23° 58' E., 0.138 chs. dist., monumented with an angle iron, 1 1/2 x 1/4 ins. firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by Wenderoth
	A fir, 17 ins. diam., bears S. 1 1/2° E., 13 lks. dist., with healed double blaze.
	Ascend over SE. slope.
39.90	Spur, slopes N. 65° E.; desc. over NE. slope.
50.50	Ravine, drains S. 80° E.; asc. over SW. slope.
55.90	Spur, slopes S. 30° E.; asc. over broken SE. slope.
58.81	Point for the center N 1/16 sec. cor. of sec. 19.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C  N 1/16        S 19  C 1983
	from which
	A fir, 29 ins. diam., bears N. 62° E., 29 lks. dist., mkd. CN 1/16 S19 BT.
	A fir, 12 ins. diam., bears N. 41 1/2° W., 22 lks. dist., mkd. CN 1/16 S19 BT.