

County Surveyor's Record, Douglas County, Oregon

17868

Subdivision of Section 19,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>Descend over NW slope.</p> <p>39.13 The center W 1/16 sec. cor. of sec. 19.</p> <p>From the center S 1/16 sec. cor. of sec. 19.</p> <p>S. 87° 07' W., on the E. and W. center line of the SW 1/4 of sec. 19.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p> <p>5.45 Spur, slopes S.; desc. over broken SW. slope.</p> <p>18.05 Spur, slopes S. 30° W.; desc. over NW. slope.</p> <p>20.29 The SW 1/16 sec. cor. of sec. 19.</p> <p>Descend over NW. slope.</p> <p>41.80 The S 1/16 sec. cor. of sec. 19 only.</p>
<p>Subdivision of Section 35, T. 30 S., R. 3 W., Willamette Meridian, Oregon</p>	
	<p>From the 1/4 sec. cor. of sec. 35 only, on the S. bdy.</p> <p>N. 0° 01' E., on the N. and S. center line of sec. 35.</p> <p>Descend over NE. slope, through heavy timber and dense undergrowth.</p> <p>17.45 Gravelled road, 20 lks. wide, bears NW. and SE.</p> <p>30.96 Point for the center 1/4 sec. cor. of sec. 35, at intersection with E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 3 W C¼ S 35 1983</p> <p>from which</p> <p style="padding-left: 40px;">A grand fir, 8 ins. diam., bears N. 65½° E., 65 lks. dist., mkd. C ¼ S 35 BT.</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears N. 5° W., 90 lks. dist., mkd. C¼ S35 BT.</p> <p>Descend over NE. slope.</p> <p>37.35 Creek, 5 lks. wide, course N. 35° W.; asc. over SW. slope.</p> <p>39.10 Barbed wire fence extends N. 30° W., and S. 30° E.</p> <p>43.80 Top of ascent, slopes W.; desc. over NW. slope.</p>