

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

17873

CHAINS

Beginning at the cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 7 ins. above ground, from which the remains of a bearing tree mkd. by Thiel:

A fir snag, 36 ins. diam., bears N. 19½° E., 30 lks. dist., with scribe marks T32S R5W S24 visible on open blaze. (Record, N. 16° E.)

and the remains of bearing trees mkd. by Wenderoth

A fir, 20 ins. diam., bears S. 70¼° E., 14 lks. dist., with healed blaze.

A root hole, bears S. 18½° W., 64 lks. dist., alongside of which is a down fir, 16 ins. diam., with healed blaze.

A fir, 21 ins. diam., bears N. 74° W., 84½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over iron pipe, with brass cap mkd.

T	32	S	R	5	W
	S 23		S 24		
	S 26		S 25		
					1983

from which new bearing trees

A fir, 12 ins. diam., bears N. 31° E., 39½ lks. dist., mkd. T32S R5W S24 BT.

A fir, 6 ins. diam., bears S. 63° W., 85 lks. dist., mkd. T32S R5W S26 BT.

N. 0° 42' W., bet. secs. 23 and 24, marking and blazing the true line.

Ascend over broken SW. slope, through heavy timber and dense undergrowth.

9.15 Dirt road, 25 lks. wide, bears S. 40° E. and S. 70° W., in curve.

13.75 Spur, slopes E.; desc. over NE. slope.

16.60 Ravine, drains NE.; asc. over broken SE. slope, changing to E. slope.

34.25 Spur ridge, bears N. 40° E. and S. 40° W.; desc. over NW. slope.

40.24 The ¼ sec. cor. of secs. 23 and 24, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of an original bearing tree: