

County Surveyor's Record, Douglas County, Oregon

17874

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 18 ins. diam., bears S. 60° E., 12 lks. dist., with chopped open blaze, no marks visible. (Record, S. 65° E.,)

and a bearing tree mkd. by Wenderoth

A fir, 21 ins. diam., bears N. 57½° W., 15 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 5 W
S 23 | S 24
1983

from which a new bearing tree

A fir, 6 ins. diam., bears N. 69½° E., 38 lks. dist., mkd. ¼ S24 BT.

N. 2° 58' W., beginning new measurement.

Descend over broken NW. slope.

7.10 Ravine, drains S. 60° W.; asc. over SW. slope.

9.05 Spur, slopes S. 80° W.; desc. over NW. slope.

11.40 Ravine, drains S. 70° W.; asc. over SW. slope, changing to W. slope.

19.97 The N. 1/16 sec. cor. of secs. 23 and 24, established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Wenderoth:

A fir, 22 ins. diam., bears S. 65° E., 15 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 42½° W., 43½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over iron pipe, with brass cap mkd.

N 1/16
S 23 | S 24
1983

N. 3° 00' W., beginning new measurement.

Ascend along W. slope.