

County Surveyor's Record, Douglas County, Oregon

17876 Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

41.85

Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionated distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 5 W

$\frac{1}{4}$ S 23
S 26
1983

From which

A fir, 6 ins. diam., bears N. $57\frac{1}{2}^\circ$ E., 68 lks. dist., mkd. $\frac{1}{4}$ S 23 BT.

A fir, 4 ins. diam., bears S. $67\frac{1}{2}^\circ$ W., 16 lks. dist., mkd. X at breast height and BT at base.

From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, bears N. $88^\circ 45'$ E., 0.20 chs. dist., monumented with an iron pipe, firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by Wenderoth

A root hole, bears N. 80° E., 102 lks. dist., alongside of which is a down fir, 33 ins. diam., with healed blaze.

A sawed fir stump, 37 ins. diam., bears S. $81\frac{1}{2}^\circ$ E., 43 lks. dist., no marks visible.

Ascend over S. slope.

42.85

Top of ascent, slopes SW.; desc. over broken SW. slope.

62.06

From this point, a corner established and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, bears North, 0.005 chs. dist., monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 12 ins. above ground, from which bearing trees mkd. by Wenderoth:

A fir, 23 ins. diam., bears S. $25\frac{1}{4}^\circ$ W., 17 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears N. $43\frac{1}{2}^\circ$ W., 17 lks. dist., with healed blaze.

80.95

Quines Creek, 10 lks. wide, course N. 40° W.; asc. over E. slope.

83.30

The cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, and subsequently perpetuated and recorded by the County Surveyor's Office, in 1967, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 22 | S 23
S 27 | S 26
1967

From which the remaining original bearing tree