

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 5 W., Willamette Meridian, Oregon

17879

## CHAINS

Land, valley floor and rolling hills  
Soil, rocky clay and gravel.  
Timber, pine, fir, cedar, oak, maple, dogwood, madrone,  
and cottonwood; undergrowth, poison oak, ceanothus,  
salal, Oregon grape, grass, and weeds

From the cor. of secs. 13, 14, 23, and 24.

N. 88° 55' W., bet. secs. 14 and 23.

Ascend over SE. slope, through heavy timber and dense  
undergrowth.

8.20 Spur, slopes N. 20° E.; desc. over NW. slope.

19.93 From this point, a corner established and recorded by  
George J. Wenderoth, Registered Land Surveyor, No. 5, in  
1953, bears North, 0.045 chs. dist., monumented with an  
iron pipe, 1 in. diam., firmly set, projecting 5 ins.  
above ground, from which bearing trees mkd. by Wenderoth:

A fir, 20 ins. diam., bears S. 33° E., 91 lks.  
dist., with healed blaze.

A fir, 22 ins. diam., bears S. 28 3/4° W., 48 lks.  
dist., with healed blaze.

28.85 Dirt road, 25 lks. wide, bears N. 60° E. and S. 60° W.

32.60 Irrigation ditch, 6 lks. wide, bears E. and W.

35.00 Fence, bears E. and W.; leave timber, enter open  
pasture, edge bears E. and W.

40.01 The 1/4 sec. cor. of secs. 14 and 23, perpetuated by  
person (s) unknown, from original evidence no longer in  
existence, and subsequently perpetuated and recorded by  
George J. Wenderoth, Registered Land Surveyor, No. 5, in  
1953, and rehabilitated and recorded by the County  
Surveyor's Office, in 1979. Mr. Donald W. Brady, a  
resident of the area for many years, furnished a signed  
statement, attached to and made a portion of these field  
notes, attesting to the corner position. The corner is  
monumented with a harrow tooth, 1 in. square, the top  
buried 6 ins. below ground, from which bearing trees  
mkd. by Wenderoth:

A cedar, 25 ins. diam., bears S. 60 1/2° E., 121 1/2 lks.  
dist., with healed blaze.

A cedar, 17 ins. diam., bears S. 9 3/4° E., 175 lks.  
dist., with healed blaze.

and a property corner established by Wenderoth, in 1968,  
and rehabilitated and recorded by the County Surveyor's  
Office, as a reference monument, in 1979.

An iron rod, 3/4 in. diam., the top buried 2 ins.  
below ground, bears N. 0° 52' E., 172 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 40 ins.  
in the ground, the top 12 ins. below surface of the  
ground, directly over harrow tooth, with brass cap mkd.