

County Surveyor's Record, Douglas County, Oregon

17880 Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 32 S R 5 W
 $\frac{1}{4}$ $\frac{S 14}{S 23}$
 1983

from which a new bearing tree

A fir, 28 ins. diam., bears N. $4 \frac{3}{4}^\circ$ W., 330 lks.
dist., mkd. $\frac{1}{4}$ S14 BT.

Corner is located at intersection of dirt roads, both 25 lks. wide, bearing N., S., and W.

From this point, the cor. of secs. 14, 15, 22, and 23, bears N. $89^\circ 35'$ W., 40.65 chs. dist., hereinbefore described.

Land, mountainous.
Soil, rocky clay.
Timber, pine, fir, cedar, oak, maple, dogwood, and madrone; undergrowth, poison oak, ceanothus, Oregon grape, manzanita salal, grass, and weeds.

From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor, No. 5, in 1953, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, from which a bearing tree mkd. by Thiel:

A fir, 31 ins. diam., bears S. 86° E., 51 lks.
dist., with chopped, healed blaze, no marks visible. (Record, S. 87° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
 $\frac{1}{4}$ $\frac{S 27}{S 34}$
 1983

from which a new bearing tree

A white fir, 17 ins. diam., bears N. $22 \frac{3}{4}^\circ$ W., 48 lks. dist., mkd. $\frac{1}{4}$ S 27 BT

Reset iron pipe alongside iron post.

S. $89^\circ 53'$ W., bet. secs. 27 and 34.

Descend over NW. slope, through heavy timber and dense undergrowth.

- 1.20 Ravine, drains N. 40° E.; asc. over broken SE. slope, changing to NE. slope.
- 14.10 Top of ascent, slopes N.; desc. over NW. slope.
- 19.30 Ravine, drains N. 45° E.; asc. over broken NE. slope, changing to N. slope.
- 32.45 Top of ascent, slopes N.; desc. over NW. slope.